

精密夹头配件
Precision Chuck Fittings




CT 夹头

C 夹头


ER 夹头

C型钻孔夹头参数 C-type Drilling Chuck Parameters:




Model 型号	∅d柄径 (mm) Handle diameter	∅D (mm)	L (mm)	B	A (mm)	最大夹持能力 Max. clamping capacity
C-4	∅1-∅4	∅8.2	24	1/4-28UNF	6	∅4
C-5	∅1-∅5	∅10.8	31.5	5/6-24UNF	8	∅5
C-6	∅1-∅6	∅13.1	36	3/8-24UNF	10	∅6
C-9	∅1-∅9	∅17	46	1/2-20UNF	14	∅9
C-12	∅2-∅12	∅21	50	5/8-18UNF	17	∅12
C-14	∅5-∅14	∅24.5	54	3/4-16UNF	21	∅14
C-16	∅5-∅16	∅31	70	M24-2.0	26	∅16

CT型攻牙夹头参数 CT-type Tapping Chuck Parameters:



Model 型号	∅d柄径 (mm) Handle diameter	∅D (mm)	L (mm)	B	A (mm)	最大夹持能力 Max. clamping capacity
CT-4	∅3-∅4	∅8.2	24	1/4-28UNF	6	M3.5×0.6
CT-5	∅3-∅5	∅10.8	31.5	5/6-24UNF	8	M4×0.7
CT-6	∅3-∅6	∅13.1	36	3/8-24UNF	10	M6×1.0
CT-9	∅3-∅7	∅17	46	1/2-20UNF	14	M8×1.25
CT-12	∅3-∅9	∅21	50	5/8-18UNF	17	M12×1.75
CT-14	∅5-∅12	∅24.5	54	3/4-16UNF	21	M14×2.0
CT-16	∅5-∅14	∅31	70	M24-2.0	26	M18×2.5

ER夹头参数 ER Chuck Parameters:



Model 型号	Clamping Range 型夹持范围														
ER8	1.0-1.5	1.5-2.0	2.0-2.5	2.5-3.0	3.0-3.5	3.5-4.0	4.0-4.5	4.5-5.0							
ER11	1.0-1.5	1.5-2.0	2.0-2.5	2.5-3.0	3.0-3.5	3.5-4.0	4.0-4.5	4.5-5.0	5.0-5.5	5.5-6.0	6.0-6.5	6.5-7.0			
ER16	2-3	3-4	4-5	5-6	6-7	7-8	8-9	9-10							
ER20	2-3	3-4	4-5	5-6	6-7	7-8	8-9	9-10	10-11	11-12	12-13				
ER25	2-3	3-4	4-5	5-6	6-7	7-8	8-9	9-10	10-11	11-12	12-13	13-14	14-15	15-16	



丝攻夹头A

铣床BT夹头

手动夹头座

气动夹头座

钻孔夹头

丝攻夹头B

